

ILED-DA-12V / ILED-DA-24V

LED Electronic Driver

Catalog #:	Type:
Notes:	

Product Specifications

Mechanical and Thermal:

Dimensions (mm) :	30mm x 43mm x 157mm
Weight	140 grams
Tc Max	90°C
Ta Max	50°C
PC plastic casing	
Terminal Block Connection	

Electrical:

Load	1-25VA
Input	90-277V 50/60Hz
Output at Max. load	8V/12V/24VDC
Power Factor	0.96
Efficiency	86%
THD max	8%
EMC (RFI)	FCC Class B/EN 55015
Harmonics	EN 61000
Immunity	EN 61547/61047
SELV	

Protection

Electronic internal resettable short circuit protection. Overload and thermal regulation.
Voltage Regulation.

Dimensions



TRANSFORMER	DESCRIPTION	CATALOG #
LED ELECTRONIC DRIVER	Load: 1-25VA. Input: 90-277V 50/60Hz. Output at Max. load 8V/12V/24VDC. NRTL listed. Dimensions: 30mm x 43mm x 157mm	ILED-DR-12V (12V) ILED-DR-24V (24V)

*Note: Specifications and dimensions subject to change without notice.

2861. E La Palma Ave. • Anaheim, CA 92806 • Phone: 1.800.961.5321 • Fax: 1.800.961.5322 • www.intenselightning.com

