

# ITLED12Y

## Fundamentals 32W LED Track Flood / Wall Wash Luminaire

JOB NAME		CATALOG NUMBER	
NOTES		TYPE	

### ELECTRICAL DATA

LED Light Engine	Delivered Lumens *	System Wattage **
L1	2545lm @ 3000K / 80 CRI	32 Watts

\* System Wattage include driver and LED Module consumption.

### FEATURES

- Extruded aluminum heatsink housing provides light weight, durability, clean lines and optimal thermal dissipation
- Pivot mounts allow rotations up to 350° horizontally and 0° to 90° vertically in both directions for maximum aiming adjustability

### LED LIGHT ENGINE

- 80+ CRI in 3000K; consult factory for additional CCT / CRI values and lead times
- LED mounted to die-cast / extruded aluminum heat sink
- 50,000 hours L70

### ELECTRICAL SYSTEM

- 120V 50/60Hz input
- Class 2 power supply
- Over voltage, over current and short circuit protection
- This product complies with IEEE C62.41 for surge endurance up to 2.5KV. Additional surge protection recommended. Damage from power surge is not covered by warranty.

### DIMMING

- (ELV) reverse phase control dimmers 120V only
- Dimmable 100 - 10%

### TRACK COMPATIBILITY

Track luminaire is designed for use with the following track systems:

- Single Circuit / Single Neutral 120V
- Two Circuit / Single Neutral 120V (No Dimming)
- J-Type Single / Two Circuit 120V
- L-Type Single / Two Circuit 120V

### LOUVER


Luminaire available with optional louver, must specify suffix **-AL**, factory installed.

### LISTING / WARRANTY



- ETL Listed to US and Canadian standards for damp locations
- 5-Year Intense LED Limited Warranty



### fundamentals™



Shown with optional louver



### Part Number (Example: ITLED12YL1308W)

Luminaire	Wattage	CCT / CRI¹	Finish	Adapter	Accessory
ITLED12Y	L1 (32 Watts)	308 (3000K / 80 CRI)	W (White) B (Black)	blank (Intense Single / Two Circuit 120V) -J (J-Type Adapter 120V) -L (L-Type Adapter 120V)	-AL (Louver)

Notes:

1. Consult factory for alternate CCT / CRI options