






## **Small Form Factor**

Downlighting, Pendants, Track & Recessed Multiples





# An Entire Family Built On A Single Platform

Bound together by a common platform, the MX product line allows for uniform and consistent lighting throughout an entire space making it the ideal product line for many applications including retail, commercial, hospitality and residential. This diverse line delivers smooth, beautiful illumination and impressive performance that delivers up to 1850lm.




мх	Downlighting					
Туре	3.5" Downlight	3.5" Square Downlight	3.5" Adjustable	3.5" Square Adjustable	3.5" Wall Wash	3.5" Square Wall Wash
Remodel Option	Yes	Yes	Yes	Yes	Yes	Yes
Lumens	950-1850lm	750-1850lm	950-1850lm	900-1800lm	470-908lm	536-1025lm
ССТ	2700К, 3000К, 3500 or 4100К   Class A 3500К   Crisp White 3000К					
CRI	82/92 CRI					
Optics	12°, 24°, 36° & 50° Uniform Wall Wash Distribution					
Controls			ELV, 0-10V, Lut	ron, DALI, DMX		











Pendant		Track L	ighting	Multiples		
			P. C.	00	100	00
9", 12" & 15" Pendant	9", 12" & 15" Square Pendant	MX Track Head	MXH Track Head	1-4 Head & 10"x10" Recessed	1-4 Head & 10"x10" Semi Recessed	1-4 Head & 10"x10" Flush Mount
	n	′a		Yes		
900-1525lm	850-1400lm	950-1	950-1700lm		950-1700lm Per Head	
2700K, 3000K, 3500 or 4100K   Class A 3500K   Crisp White 3000K						
82/92 CRI						
12°, 24°, 36° & 50°						
ELV, 0-10V, Lutron, DALI, DMX		ELV (0-10V C	Canopy Only)	ELV, 0-10V, Lutron, DALI, DMX		







# Unified Design Across The Board

## Color Reliability

- 2 SDCM Binning ensures color consistency across luminaires
- Available in 2700K, 3000K, 3500K & 4100K
- High CRI and modified spectrum CCT's (82, 92, Class A & Crisp White)













35 4100k

## Precision Optics

- Precision beam control and aiming via custom TIR optical technology
- Field changeable optics across entire family
- High center beam spot with up to 24,500 CBCP

Degree







Degree













## Multiple Control Options

- Standard 0-10V 1% dimming, ELV, DALI and DMXR
- Tunable White: Selectable CCT's from warm to cool white
- Dynamic Dim: Warms along the black body curve
- Deep 0.1% dimming

.1% **DIMMING** 

0-10V eldoLED **RDM**  DIMMING

LUT 0-10V

DALI





## Flexible Design

- Single family platform with shared optics, LED engine and architectural finishes
- Plug and play quick connect on frame and LED engine ensures easy installation
- Downlight, adjustable and wall wash mechanisms are all field interchangeable for easy luminaire conversion

**Scene-Setting Accessories** Accessories include black hex louver, prismatic spread, linear spread, and Solite lens.

**Quick Connect Provides** Plug & Play Installation Shared LED **Platform For Consistent** Performance

Field Interchangeable Between Downlight, Adjustable & Wall Wash Mechanisms

# Downlighting

The MX Downlight provides a dynamic solution for consistent lighting and limitless design possibilities.

Inside the 3.5" aperture resides a compact yet powerful light engine capable of adapting to a variety of commercial, hospitality, residential and retail lighting needs. The downlight, adjustable and wall wash mechanisms are all field interchangeable for easy on-site changes if needed.

#### Lumen Packages





**MXG2D** 3.5" Downlight Round or Square



MXG2A 3.5" Adjustable Round or Square



**MXG2W** 3.5" Wall Wash Round or Square



### Work Smarter Not Harder

#### **Extensive Housing Options**




MX downlight housings are available in New Construction, Air-Tight IC, Chicago Plenum, Non-IC and Remodel options

#### Adjustability From Below The Ceiling




Horizontal Adjustments



Vertical Adjustments


#### Die-Cast Aluminum Trims





Solid aluminum die-cast construction on both trim and trimless

#### Extended Collars For Thick Ceilings



Accommodates ceiling thicknesses from 5/8 to 2 inches



# A Trim for Every Space

Featuring specification grade die-cast aluminium trims, MX is designed to enhance any environment. Available in round, square, pinhole and in trim or trimless these beautiful finishes include white, black, satin nickel, antique bronze and wheat.

#### Architectural Finishes





















Downlight








Wall Wash Pinhole

Trım Ty	pes
---------	-----

пт турез	Trim	med	Trim	ıless	Wood	Ceiling	Flat Mount		Non Conductive	
Aperture Type	Round	Square	Round	Square	Round	Square	Round	Square	Round	Square
1 ½-INCH STANDARD TRIM										
Downlight	✓	✓	✓	✓	-	-	-	-	-	-
Lensed Downlight	✓	✓	✓	✓	-	-	-	-	-	-
Pinhole Downlight	✓	✓	✓	✓	-	-	-	-	-	-
Lensed Pinhole Downlight	✓	✓	✓	✓	-	-	-	-	-	-
Adjustable	✓	✓	✓	✓	-	-	-	-	-	-
Pinhole Adjustable	✓	✓	✓	✓	-	-	-	-	-	-
Wall Wash	✓	✓	✓	✓	✓	✓	-	-	-	-
1/2-INCH REGRESS TRIM										
Downlight / Adjustable	✓	✓	<b>√</b>	✓	✓	<b>✓</b>	-	-	-	-
Lensed Downlight / Adjustable	✓	✓	✓	✓	✓	✓	-	-	✓	✓
Pinhole Downlight / Adjustable	✓	✓	✓	✓	✓	✓	✓	✓	-	-
Lensed Pinhole Downlight / Adjustable	✓	✓	✓	✓	✓	✓	✓	✓	-	-






0.15" trim thickness



**→ √**1/2"

Half-Inch Regressed

















# Architectural Pendants

MX Pendants are elegant, architectural accent luminaires built on the same platform to provide uniform and consistent performance across the entire family. Modular ingenuity transforms the expansive options and aesthetics of the award-winning downlight into beautifully finished round and square pendants.

#### Lumen Packages







#### Pendant Finishes








## Compact Performance

- Interchangeable precision TIR optics ranging from 12° to 50°
- 3 elegant sizes in round and square aperture (9, 12 & 15-Inch)
- Available in multiple mounting and control options
- Utilizes the same trimless reveal as downlights

#### Pendant Type



#### **Mounting Options**



	9in	12in	15in
LUMENS			
L0: 950lm	✓	✓	✓
L1: 1300lm	✓	✓	✓
L2: 1550lm	✓	✓	✓
CONTROLS			
ELV	✓	✓	✓
0-10V	✓	$\checkmark$	✓
eldoLED	-	-	✓
Lutron	-	-	✓
DALI	-	-	✓
ENHANCED COLOR			
Class A	✓	✓	✓
CrispWhite	✓	✓	✓
Tunable White	-	-	✓
Dynamic Warm Dim	-	-	✓

#### Trim Finishes











## Track Heads

Beautifully designed and constructed, the MX track head is available in vertical and horizontal configurations. High performance field changeable optics ranging from 12° spot to 50° wide flood precisely deliver quality light where necessary. A discreet accessory holder accommodates two forms of media.

#### Lumen Packages





MXG2 Vertical Accent



MXHG2 Horizontal Accent



**MXG2C**Canopy Mounted Luminaire



Available Finishes







# GU5.3 / GU10 Options

The MX MR16 track heads are available in vertical and horizontal configurations that utilize MX construction and accessories. An innovative, integral sleeve allows for easy lamp centering and perfect alignment.

#### GU5.3/GU10 Lamp Type (12V only)

	1 31	
GU5.3 LED		■ 15W Max.
GU5.3 Halogen		■ 35W Max.
GU10 LED		■ 15W Max.
GUI10 Halogen		■ 35W May



GU10/GU5.3 Downlight



GU10/GU5.3 Recessed Multiples



GU10/GU5.3 Track & Canopy



# Recessed Multiples

Based on the award-winning MX track head, MX recessed and semi-recessed multiples are available in 1, 2, 3, or 4 lamp configurations and a 10"x10" square. Featuring a frame-in design, MX multiples are offered with a new construction or remodel frame in trim or trimless options.

#### Lumen Packages






MXG2RTR Recessed Multiple



MXG2SRTR Semi Recessed Multiple



MXG2FMTR Flush Mount Recessed Multiple







## Ease of Installation

The MX recessed multiple frame-in is designed with ease of installation in mind. The junction box is accessible, if from below the ceiling, and it is equipped with a quick connect for plug and play trim assembly installation. The frame is constructed of 18 gauge steel, powder coated black, and ships with a perforated mesh frame for adherence to joint compound for the optional trimless version.



#### Frame-In Kit

The MX frame-in kit can ship before the trim, reducing installation time.



#### Remodel Frame-In

Remodel frame-in kit employs a quick connect and heavy duty torsion springs to ensure easy and quick installation.

•	Trimmed	Trimless	Flush Mount
RECESSED			
1 Lamp	MXG2RTR1	MXG2RTL1	MXG2FM1
2 Lamp	MXG2RTR2	MXG2RTL2	MXG2FM2
3 Lamp	MXG2RTR3	MXG2RTL3	MXG2FM3
4 Lamp	MXG2RTR4	MXG2RTL4	MXG2FM4
10" x 10"	MXG2RTRSQ4	MXG2RTLSQ4	MXG2FMSQ4
SEMI RECESSED			
1 Lamp	MXG2SRTR1	MXG2SRTL1	-
2 Lamp	MXG2SRTR2	MXG2SRTL2	-
3 Lamp	MXG2SRTR3	MXG2SRTL3	-
4 Lamp	MXG2SRTR4	MXG2SRTL4	-
10" x 10"	MXG2SRTRSQ4	MXG2SRTLSQ4	-



#### LED Module Kit:

Example: MXG2ML02712

	Series
MXMG2	MX G2 Module
	Wattage
L0	10W
L1	16W
L2	20W
L3	26W
	CCT / CRI
27	2700K / 82 CRI
279	2700K / 92 CRI
30	3000K / 82 CRI
309	3000K / 92 CRI
35	3500K / 82 CRI
41	4100K / 82 CRI
CA35	Class A 3500K
CW30	CrispWhite 3000K
	Optic
12	12° Spot
24	24° Narrow Flood
36	36° Flood
50	50° Wide Flood



## MR16 Module Kit: **Example:** MXM-GU53

-	
	SERIES
MXM	MX Module
	BASE TYPE
-GU53	12V MR16
-GU10	120V MR16



#### Mechanism Kit:

Mechanism kit to convert between MX Downlight, Adjustable and Wall Wash.

ITEM NUMBER	DESCRIPTION
IP-MXDN	MX Downlight Mechanism
IP-MXAJ	MX Adjustable Mechanism
IP-MXWW	MX Wall Wash Mechanism



#### LED Optics:

For use with any MX LED Downlight or LED Adjustable fixture.

ITEM NUMBER	DESCRIPTION
IP-0P4712	12° Spot
IP-0P4724	24° Narrow Flood
IP-0P4736	36° Flood
IP-0P4750	50° Wide Flood



#### ACCESSORY HOLDER:

Holds two filter Media.

**ITEM NUMBER** 

LH47	Accessory Holder, Black

**DESCRIPTION** 



#### Filter Media:

For use with MX Downlight or Adjustable fixture in conjunction with LH47 accessory holder (holds two filter media).

ITEM NUMBER	DESCRIPTION
PFLMB-47	Hex Louver, Black
PFL4-47	Solite Lens
PFL2-47	Linear Spread Lens
PFL1-47	Prismatic Spread Lens



#### MX Wet Location Kit:

Converts downlight trims into wet location trims. Wet location kit for MX Downlight only.

**Example:** MXL-RD-SL

	SERIES
MXL-RD	Round Downlight
MXL-SD	Square Downlight
MXL-RP	Round Pinhole
MXL-SP	Square Pinhole
	LENS TYPE
-SL	Solite
-CR	Clear Tempered
-FR	Frosted



# IN POPULAR CULTURE











RICHARD NIXON BEYOND PEACE











Intense Lighting 3340 E. La Palma Ave. Anaheim, CA 92806

tel 714 630-9877 fax 714 630-9883

info@intenselighting.com www.intenselighting.com

A Leviton Company www.leviton.com

Printed in the U.S.A ©2017. Intense Lighting, LLC. All Rights Reserved.

INT0317-MX-2