

SD8DRR / IC830

8" SD LED Remodel Downlight

JOB NAME		CATALOG NUMBER	
NOTES		TYPE	

ELECTRICAL DATA

LED Light Engine	System Wattage* @ 120V	CCT	Nominal Delivered Lumens**	Efficacy
L0	8W	3500K	750 lm	94 lm/W
L1	10W	3500K	1000 lm	102 lm/W
L2	14W	3500K	1500 lm	110 lm/W
L3	19W	3500K	2000 lm	108 lm/W
L4	23W	3500K	2500 lm	111 lm/W
L5	28W	3500K	3000 lm	110 lm/W
L6	33W	3500K	3500 lm	108 lm/W
L7	38W	3500K	4000 lm	108 lm/W

*System Wattage includes driver and LED Module consumption. | **Delivered lumen output will vary depending on CCT selection.

LED MODULE / OPTICS

- 80/90 CRI at 2700K, 3000K, 3500K, 4000K with 2 SD CM
- 70% lumen maintenance at 50,000 hours
- 30° Narrow Spot, 50° Flood or 70° Wide Flood

ELECTRICAL SYSTEM

- Dedicated voltage options of 120V, 277V or 347V must be specified in catalog code.
- Phase dimming available in 120V only
- 347V available with Osram 0-10V 1% Dimming only

FRAME CONSTRUCTION

Heavy duty galvanized steel frame with a large access junction box. ETL listed for through wiring. LED light engine and driver are accessible from above or below ceiling.

INSTALLATION

Three high tensions springs secure fixture into ceiling with up to 5/8" thickness. Max. ambient temperature: 95°F (35°C).

REFLECTOR

Specification grade reflector with 1.2mm thickness. Reflector available in clear specular, haze or white. Architectural, discrete polished self flange standard. Optional painted white flange is available. Meets RP-1 requirements with controlled light distribution at a 50° cut off.

DIMMING



- 0-10V Dimming 1%
- Phase Dimming 120V only, Forward 1% / Reverse 5%
- EldoLED 0-10V 0.1% or 1%
- Lutron® LDE1 Hi-Lume 1% EcoSystem LED driver with Soft-on, Fade-to-Black dimming technology
- DMX512 RDM 0.1%

intellect™


- Integrated control system provides occupancy and light level detection, and controls the load directly by the power control module Integrated intelligent fixture controls
- Visit Leviton [intellect™](#) for more info

LISTING/WARRANTY

- ETL listed to US and Canadian standards for damp locations.
- 5-Year Intense LED Limited Warranty
- ENERGY STAR® Qualified⁹




8 5/16"



12"

8 5/16"



Sensor Control Module

1 1/4"



Ceiling Cut Out: 8"
Maximum Ceiling Thickness: 1 1/4"

Housing Part Number (Example: SD8DRRL4359-D101-NF)

Housing	LED Module	CCT / CRI	Dimming	Voltage	Optic
SD8DRR	L0 ¹ (8W)	27 (2700K / 80 CRI)	-D101 (Osram 0-10V 1%)	blank (120V)	-NF (30°)
	L1 (10W)	279 (2700K / 90 CRI)	-IE ³ (Intellect Wireless 1%)	27 (277V)	-FL (50°)
	L2 (14W)	30 (3000K / 80 CRI)	-DIM ^{4,5} (Phase Dimming)	34 ⁸ (347V)	-WF (70°)
	L3 (19W)	309 (3000K / 90 CRI)	-ED10V1 (eldoLED 0-10V 1%)		
	L4 (23W)	35 (3500K / 80 CRI)	-ED10V01 (eldoLED 0-10V 0.1%)		
	L5 (28W)	359 (3500K / 90 CRI)	-LUT ⁶ (Lutron® LDE1 EcoSystem 1%)		
	L6 (33W)	40 (4000K / 80 CRI)	-DMXR ⁷ (DMX512 RDM 0.1%)		
L7 ² (38W)	409 (4000K / 90 CRI)				

Reflector Part Number (Example: IC830HZ-SF)

Reflector	Reflector / Flange Finish
IC830	C-SF (Clear, Self-Flanged)
	C-SFW (Clear, Self-Flanged White)
	HZ-SF (Haze, Self-Flanged)
	HZ-SFW (Haze, Self-Flanged White)
	W-SF (White, Self-Flanged)

Notes:

- L0 only available with -D101
- 347V Not available with L7 option
- Intellect not available with eldoLED, Lutron, Dali or DMX Dimming (Integrated intellect control system includes sensor and power pack, keypad Room Controller must be specified separately)
- Not available in L1, L2 or L7
- Not available in 277V
- Lutron not available in L1 & L7
- DMX512 RDM not available in L1 & L2
- 347V only available with Osram 0-10V 1% Dimming
- ENERGY STAR® Qualified (0-10V & ELV only. Excludes CCT/CRI options 279, 309 & 359)

SS-DOWNLIGHTING LUM-892123 P.45

INTENSE LIGHTING | 3340 E La Palma Ave, Anaheim, CA 92806 | tel 714 630-9877 | fax 714 630-9883

For Intense Lighting's limited product warranty, go to www.intenselighting.com. For a printed copy of the warranty, you may call 800 961-5321.

© 2023 Intense Lighting, LLC. All rights reserved. Note: This document is subject to change without notice.

intense[®] | a LEVITON[®] company
LIGHTING

SD8DRR / IC830

8" SD LED Remodel Downlight

JOB NAME		CATALOG NUMBER	
NOTES		TYPE	

Electrical Table					
Lumen Package	Voltage	Wattage	VA	Input Current	Power Factor
L0	120	7.43	7.99	0.07	0.930
	277	8.41	11.87	0.04	0.709
L1	120	9.75	10.37	0.09	0.94
	277	10.82	14.18	0.05	0.76
L2	120	13.71	14.35	0.12	0.96
	277	14.85	18.06	0.07	0.82
L3	120	18.27	18.54	0.15	0.99
	277	19.77	22.92	0.08	0.86
L4	120	22.74	23.04	0.19	0.99
	277	24.09	27.31	0.10	0.88
L5	120	27.18	27.44	0.23	0.99
	277	28.93	32.00	0.12	0.90
L6	120	32.76	32.84	0.27	1.00
	277	34.09	36.72	0.13	0.93
L7	120	37.71	37.79	0.31	1.00
	277	38.86	41.77	0.15	0.93

SD8DRR / IC830

8" SD LED Remodel Downlight

JOB NAME		CATALOG NUMBER	
NOTES		TYPE	

SD8DRRL1358 IC830C


CCT MULTIPLIERS:

	80 CRI	90 CRI
2700K	(x 0.92)	(x 0.79)
3000K	(x 0.98)	(x 0.79)
3500K	(x 1.00)	(x 0.82)
4000K	(x 1.01)	(x 0.84)

FINISH MULTIPLIERS

	30°	50°	70°
Clear	(x 1.00)	(x 1.00)	(x 1.00)
Haze	(x 0.96)	(x 0.96)	(x 0.88)
White	(x 0.96)	(x 0.97)	(x 0.90)

-NF (30° Narrow Flood)




Footcandles at Nadir

Watts: 10 LPW: 99.1
Lumens: 991 CCT: 3500K

Luminance	
Degree	CBCP
0°	3439
5°	3047
15°	1453
25°	424
35°	136
45°	15

-FL (50° Flood)




Footcandles at Nadir

Watts: 10 LPW: 106
Lumens: 1060 CCT: 3500K

Luminance	
Degree	CBCP
0°	1696
5°	1600
15°	1421
25°	826
35°	176
45°	15

-WF (70° Wide Flood)



Footcandles at Nadir

Watts: 10 LPW: 102
Lumens: 1020 CCT: 3500K

Luminance	
Degree	CBCP
0°	1338
5°	1223
15°	889
25°	609
35°	458
45°	112

SD8DRRL2358 IC830C


CCT MULTIPLIERS:

	80 CRI	90 CRI
2700K	(x 0.92)	(x 0.79)
3000K	(x 0.98)	(x 0.79)
3500K	(x 1.00)	(x 0.82)
4000K	(x 1.01)	(x 0.84)

FINISH MULTIPLIERS

	30°	50°	70°
Clear	(x 1.00)	(x 1.00)	(x 1.00)
Haze	(x 0.96)	(x 0.96)	(x 0.88)
White	(x 0.96)	(x 0.97)	(x 0.90)

-NF (30° Narrow Flood)




Footcandles at Nadir

Watts: 14 LPW: 106.1
Lumens: 1486 CCT: 3500K

Luminance	
Degree	CBCP
0°	5159
5°	4571
15°	2179
25°	636
35°	204
45°	23

-FL (50° Flood)




Footcandles at Nadir

Watts: 14 LPW: 113.6
Lumens: 1590 CCT: 3500K

Luminance	
Degree	CBCP
0°	2544
5°	2400
15°	2131
25°	1239
35°	264
45°	23

-WF (70° Wide Flood)



Footcandles at Nadir

Watts: 14 LPW: 109.3
Lumens: 1530 CCT: 3500K

Luminance	
Degree	CBCP
0°	2006
5°	1834
15°	1333
25°	913
35°	686
45°	168

SD8DRR / IC830

8" SD LED Remodel Downlight

JOB NAME		CATALOG NUMBER	
NOTES		TYPE	

SD8DRRL3358 IC830C


CCT MULTIPLIERS:

	80 CRI	90 CRI
2700K	(x 0.92)	(x 0.79)
3000K	(x 0.98)	(x 0.79)
3500K	(x 1.00)	(x 0.82)
4000K	(x 1.01)	(x 0.84)

FINISH MULTIPLIERS

	30°	50°	70°
Clear	(x 1.00)	(x 1.00)	(x 1.00)
Haze	(x 0.96)	(x 0.96)	(x 0.88)
White	(x 0.96)	(x 0.97)	(x 0.90)

-NF (30° Narrow Flood)




Footcandles at Nadir

Watts: 19 LPW: 104.2
Lumens: 1979 CCT: 3500K

Luminance	
Degree	CBCP
0°	6866
5°	6083
15°	2900
25°	846
35°	271
45°	30

-FL (50° Flood)




Footcandles at Nadir

Watts: 19 LPW: 111.4
Lumens: 2117 CCT: 3500K

Luminance	
Degree	CBCP
0°	3386
5°	3194
15°	2837
25°	1649
35°	351
45°	30

-WF (70° Wide Flood)



Footcandles at Nadir

Watts: 19 LPW: 107.2
Lumens: 2037 CCT: 3500K

Luminance	
Degree	CBCP
0°	2671
5°	2442
15°	1775
25°	1216
35°	914
45°	224

SD8DRRL4358 IC830C


CCT MULTIPLIERS:

	80 CRI	90 CRI
2700K	(x 0.92)	(x 0.79)
3000K	(x 0.98)	(x 0.79)
3500K	(x 1.00)	(x 0.82)
4000K	(x 1.01)	(x 0.84)

FINISH MULTIPLIERS

	30°	50°	70°
Clear	(x 1.00)	(x 1.00)	(x 1.00)
Haze	(x 0.96)	(x 0.96)	(x 0.88)
White	(x 0.96)	(x 0.97)	(x 0.90)

-NF (30° Narrow Flood)




Footcandles at Nadir

Watts: 23 LPW: 107.6
Lumens: 2474 CCT: 3500K

Luminance	
Degree	CBCP
0°	8586
5°	7670
15°	3626
25°	1058
35°	339
45°	38

-FL (50° Flood)




Footcandles at Nadir

Watts: 23 LPW: 115.1
Lumens: 2647 CCT: 3500K

Luminance	
Degree	CBCP
0°	4234
5°	3994
15°	3547
25°	2062
35°	439
45°	37

-WF (70° Wide Flood)



Footcandles at Nadir

Watts: 23 LPW: 110.7
Lumens: 2547 CCT: 3500K

Luminance	
Degree	CBCP
0°	3339
5°	3053
15°	2219
25°	1520
35°	1142
45°	280