# MR16-MXGU10NTC

MX MR16 LED GU10 Canopy Mounted Luminaire

# NOTES CATALOG NUMBER TYPE

## **FEATURES**

- Uses MX accessories with LED lamps
- Easy lamp access with quarter turn cap
- MX construction and quality finishes

## LAMP (ORDERED SEPARATELY)

- 120V MR16 GU10 LED 15W max.
- 120V MR16 GU10 Halogen 35W max.

#### HOUSING

Constructed using heavy duty die-cast and extruded aluminum. Lamp is secured in a 6U10 ceramic twist and lock socket. The die-cast cap has a cold rolled steel alignment ring to center MR16 lamp. Luminaire accommodates lamp diameter up to 1.97" (50.1mm) and MOL of 2.18" (55.3mm). Horizontal adjustability up to 358° and vertical adjustability up to 258°.

#### SOCKET

**GU10** Ceramic Twist and Lock

#### MOUNTING

Mounts to a standard 4" square or octagon junction box

#### **ACCESSORIES**


Luminaire will accommodate a maximum of (2) accessories, an accessory holder is required. Integral snoot is compatible with accessory holder. Snoot's interior is black, black accessory holder is recommended.


#### LISTIN

- ETL Listed to US and Canadian standards for dry locations
- Fixture can be labeled with reduced maximum wattage rating to facilitate energy code compliance consult factory









Horizontal Adjustability: 358° Vertical Adjustability: 258°

# Example: MR16-MXGU10CW

Luminaire	Finish	Option
MR16-MXGU10NTC	W (White) B (Black) SV (Silver)	-\$1 (Integral 1" Snoot, Black Interior)

# Accessories (Accessory holder is required)

☐ LH47	(Accessory Holder, Black)
LH47W	(Accessory Holder, White)
☐ PFLMB-47	(Hex Louver, Black)
☐ PFL1-47	(Prismatic Spread Lens)
☐ PFL2-47	(Linear Spread Lens)
PFL4-47	(Soft Focus Lens)

Notes:

Snoot is integral to fixture and factory installed. Snoot's interior is black and compatible with accessory holder, black accessory holder recommended.

